

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**CLAIMS LISTING**

1. (Previously presented) A sensing assembly for use with a tape drive employing a single reel equipped with a takeup leader for interconnecting with a tape cartridge leader connected to a length of tape media located within a tape cartridge, to determine if said tape cartridge leader disconnects from said takeup leader during unloading of said tape cartridge, so that said tape cartridge can be removed from said tape drive without damaging said length of tape media, comprising:

means for disconnecting said takeup leader from said tape cartridge leader prior to removing said tape cartridge from said tape drive; and

at least one leader position detecting means to detect a position of at least one of said tape cartridge leader and said takeup leader following said disconnect, said position being used to determine if said tape cartridge leader disconnects from said takeup leader, comprising:

a means for sensing movably located a distance from a tape path; and

a means for moving said movable sensing means from an initial position into said tape path to detect said position of at least one of said takeup leader and said tape cartridge leader.

2. (Original) The sensing assembly of claim 1 further comprising:

a processing means, responsive to said detected position of said at least one of said takeup leader and said tape cartridge leader, for determining if said tape cartridge leader disconnects from said takeup leader.

Claim 3 (Canceled)

4. (Currently amended) The sensing assembly of claim 1 wherein said sensing means is rotatable and comprises:

Serial No. 10/678,781

Amendment And Remarks Responsive To  
Office Action Mailed 07/02/04

Page 5 of 14

298228v1

a means for sensing a rotational position of said rotatable sensing means, said rotational position for determining if said tape cartridge leader disconnects from said takeup leader.

5. (Currently amended) A test fixture for use in testing a tape drive employing a single reel equipped with a takeup leader for interconnecting with a tape cartridge leader connected to a length of tape media located within a tape cartridge, said takeup leader and said tape cartridge leader defining a tape path, to determine if said tape cartridge leader disconnects from said takeup leader during unloading of said tape cartridge, comprising:

a connecting means for removably connecting said tape drive to said test fixture;

means for disconnecting said takeup leader from said tape cartridge leader for removing said tape cartridge from said tape drive; and

at least one leader position detecting means to detect a position of at least one of said tape cartridge leader and said takeup leader in said tape path following said disconnect, said position being used to determine if said tape cartridge leader disconnects from said takeup leader.

6. (Original) The test fixture of claim 5 further comprising:

a processing means, responsive to said detected position of said at least one of said takeup leader and said tape cartridge leader, for determining if said tape cartridge leader disconnects from said takeup leader.

7. (Currently amended) The test fixture of claim 5, wherein said at least one leader position detecting means comprises:

a ~~movable~~ means for sensing movably insertable into said tape drive a distance from a tape path with said tape drive;

a means for moving said movable sensing means from an initial position into said tape path to detect said position of at least one of said takeup leader and said tape cartridge leader for determining if said tape cartridge leader disconnects from said takeup leader.

Serial No. 10/878,781

Amendment And Remarks Responsive To  
Office Action Mailed 07/02/04

Page 6 of 14

298228v1

8. (Original) The sensing assembly of claim 7, wherein said sensing means is rotatable and comprises:

a means for sensing a rotational position of said rotatable sensing means said rotational position for determining if said tape cartridge leader disconnects from said takeup leader.

9. (Original) The test fixture of claim 7, wherein said movable sensing means comprises:

a rotatable member extending downward into said tape drive said distance from said tape path; and

a means for sensing connected with said rotatable member for sensing a rotational position of said rotatable member.

10. (Currently amended) A sensing assembly for use with a tape drive employing a single reel equipped with a takeup leader for interconnecting with a tape cartridge leader connected to a tape media located within a tape cartridge, to determine if said tape cartridge leader disconnects from said takeup leader during unloading of said tape cartridge from said tape drive, comprising:

a disconnection apparatus for disconnecting said tape cartridge leader from said takeup leader prior to removing said tape cartridge from said tape drive;

a sensing device for sensing a position of a one of said tape cartridge leader and said takeup leader following said disconnect, said sensing device comprising:

a rotatable sensing means located a distance from a tape path;

a means for moving said ~~movable~~ rotatable sensing means from an initial position into said tape path to detect said position of said takeup leader; and

a means for sensing a rotational position of said rotatable sensing means, said rotational position for determining if said tape cartridge leader disconnects from said takeup leader; and

a processor responsive to said sensed position of said takeup leader for determining if said tape cartridge leader disconnects from said takeup leader.

Serial No. 10/678,781

Amendment And Remarks Responsive To  
Office Action Mailed 07/02/04

Page 7 of 14

298228v1

## Claim 11 (Canceled)

12. (Currently amended) A method for determining if a tape cartridge leader connected to a length of tape media within a tape cartridge disconnects from a takeup leader within a tape drive employing a single reel, said takeup leader and said tape cartridge leader defining a tape path, during unloading of said tape cartridge, comprising the step of:

(a) executing a disconnection operation to disconnect said tape cartridge leader from said takeup leader;

(b) sensing a position of [[a]] one of said tape cartridge leader and said takeup leader in said tape path following said disconnect operation; and

(c) determining a connection status of said tape cartridge leader from said takeup leader.

13. (Original) The method of claim 12, wherein said connection determination step comprises the steps of:

determining a change in position of one of said tape cartridge leader and said takeup leader after said disconnection operation; and

comparing said position change with a threshold to determine if said tape cartridge leader and said takeup leader are disconnected.

14. (Original) The method of claim 12, further comprising the step of:  
alerting an operator of a disconnection failure in response to a determination that the disconnection failed.

15. (Original) The method of claim 12, wherein the position sensing step further comprises the steps of:

positioning a movable sensing assembly a distance from a tape path;

moving said movable sensing assembly into said tape path; and

sensing a position of said movable sensing assembly to determine if said tape

cartridge leader successfully disconnected from said takeup leader.

Serial No. 10/678,781

Amendment And Remarks Responsive To  
Office Action Mailed 07/02/04

Page 9 of 14

298228v1

**Amendments to the Drawings:**

The attached sheets of drawings include changes to Figures 7 and 10. These sheets, which include Figures 7 and 10, replace the original sheets including Figures 7 and 10. In Figure 7, a retractable arm 323 has been added and in Figure 10 a test fixture 120 and a connecting means 121 have been added.

Attachment: Replacement Sheets  
Annotated Sheets Showing Changes

Serial No. 10/678,781

Page 10 of 14

Amendment And Remarks Responsive To  
Office Action Mailed 07/02/04

298228v1